



NEXT GENERATION SD-WAN

is a transformational way to architect, deploy and operate corporate WANs, as it provides a simplified way of deploying and managing remote branch office connectivity in a cost-effective way.

VIRTUAL WAN FABRIC

- Secure overlay fabric
- Transport independence
- Network segmentation

SD-WAN GATEWAY

- Local policy enforcement
- WAN path selection, network QoS, firewall, service chaining
- Telemetry feedback loop to/from SD-WAN controller

SD-WAN CONTROLLER


- Establishes and manages secure virtual overlay to sites
- Defines service chains to enable policy goals
- Manages distribution of interpreted policy to individual elements

MANAGEMENT PORTAL

- Single pane of glass for network configuration and management : cloud-hosted and on-premises
- Zero touch provisioning
- Portal where user defines global policies
- Aggregated visibility on application performance

SD-WAN FEATURES

Routing	OSPF, BGP, Static, PBR, PPPoE
User Experience	Application Prioritisation over available WAN
GPS (Optional)	Geo-Location tagging for device Geo-Fencing
VPN	Site-to-Site, L2TP, GRE, DMVPN, Remote VPN
QoS	Shaping Policy, Rate Limiter, Traffic Policies IPv4/IPv6, Traffic Shaper, DSCP Tagging
NAT	Source NAT, Destination NAT, NATv6, NAT Traversal
Network Visibility	Streaming Telemetry
Dynamic Multi-path Optimisation	KPI's-Jitter, Packet Loss, Latency, Per packet, Per Flow Load Balancing, Link Aggregation
Application Visibility	800+ Applications, Application Awareness
High Availability	VRRP, Clustering
WAN Overlay over Cloud	Public-AWS, Azure, Private
WAN Policy	WAN Aggregation, LTE and Broadband Intelligent KPI Based Switchover
Advanced LTE	LTE Primary and Bandwidth Aggregation Capability
Troubleshooting	Bandwidth Measure, IPERF, Packet Capture, Alerts, Logs



HARDWARE SPECIFICATION	
Appliance Model	iEdge-50
Deployment Mode	Branch
Core/s	2
Chipset	Intel-N2840
CPU Architecture	X86
Memory(GB)	4-8
Storage	32-128 GB SSD
Network Interfaces	Universal 2x1G
USB (Supports 3G/4G Dongle for WAN)	1x2.0 , 1x3.0
V.35 Serial Port	Supported Through External Convertor
SIM Slot (3G/4G/LTE)	1 (Optional)
Console	HDMI
WiFi	Optional (Dual Band, 802.3 b,g,n,ac Wave 1, 1x1 MIMO)
Power Supply	5V/2.5A External DC Adapter
Power Input(AC)	230 V
Power Rating(W)	12.5
Operating Temperature	-10°C to 60°C
Humidity	5%-95% Relative Humidity, Non-Condensing
Physical Dimensions (L x W x H)mm	135x135x35
Weight(kg)	0.6
Form Factor	Deskmount
AGGREGATED PERFORMANCE	
Aggregated SD-WAN Throughput(Gbps)	1.5
Aggregated IPSEC VPN Throughput(Gbps)	0.3
Packets Per Second(Mpps)	3.9
SESSIONS	
New Connections Per Second	Up to 6K
Max Sessions (IPv4 or IPv6)	Up to 32K
POLICIES	
NAT Rules	100
ROUTING	
IPv4 Forwarding Table Size	Up to 400K
IPv6 Forwarding Table Size	Up to 50K
QOS	
Number of QoS Policies	500
DSCP Marking by Policy	Yes
IPSEC VPN	
Site-to-Site	100
INFINXT REMOTE ACCESS VPN	
Max Tunnels (Client Based IPSec)	125
HIGH AVAILABILITY	
Device Count	2



**Infinity
labs**

Registered Office :
Teerth-Technospace, C-609,
Bangalore-Mumbai Highway, Baner,Pune, IN – 411045
Website : www.infinitylabs.inEmail: sales@infinitylabs.in

- Founded in 2014, Infinity Labs is one of the fastest growing Technology Consulting & Software Solutions.
- Serving customers across the Globe (India, US, UK & Middle East)
- Solutions customised for Telecom, Banking, Media, Retail, Education & Government verticals